

21.5" High Definition Panoramic Display

Key Features

- 21.5" Color Active Matrix Liquid Crystal Display
- High Resolution 1920 x 1080
- Designed and Built to Military Standards
- VGA, DVI-D, Composite Video
- Anti-Reflective Protective Window
- Wide Viewing Angle ± 178 Degrees




Model: REP-21HDW-115TV

The REP-21HDW-115TV is Epsilon Systems' 21.5" display offering significant benefits with respect to dimensions, ruggedization and video quality. The 21HDW combines unmatched mechanical integrity with exceptionally low weight to provide a unique, rugged display solution, especially for applications where space and weight are critical.

The REP-21HDW-115TV features a 21.5" Active Matrix Liquid Crystal Display 1920 x 1080 offering excellent performance in terms of brightness, crispness, contrast and viewing angle. The bezel and mounting can be customized to address virtually any mounting need in any application. Additionally, the REP-21HDW-115TV combines this high level of performance and versatility with a very competitive price/performance value.

Epsilon Systems' displays have been designed and qualified for application in the most hostile environments. Epsilon Systems' rugged displays are well suited for specific naval combat, army and airborne applications.



BACK ISOMETRIC



21.5" High Definition Panoramic Display

Contact

Brian Gallatin

Vice President & GM,
Advanced Products Group

757-961-4526

FlatPanels@epsilonsystems.com

5482 Complex Street, Suite 109
San Diego, CA 92123

619-702-1700

Headquarters and Corporate Office
9242 Lightwave Ave., Suite 100
San Diego, CA 92123

TECHNICAL SPECIFICATIONS


Active Display Area	21.5" TFT Active Matrix LCD
Display Resolution	1920 x 1080
LCD Technology	LED Backlighting
Input Interface	VGA (HD15) DVI-D, Composite Video
Brightness	250 cd/m ² (Minimum)
Viewing Angle	± 178 Degrees All Directions (Typical)
Contrast Ratio	1000:1 (Typical)
Display Colors	16M
Power Supply	115 VAC (-48 VDC option); 104 Watts (Typical)
Model Number	REP-21HDW-115TV
User Controls	Brightness/Dim, Power, Menu, Curser Up/Down/Left/Right

DESIGNED TO MEET RIGOROUS MILITARY SPECIFICATIONS


MIL-STD-167-1, Type 1	Vibration
MIL-STD-810	Environmental
MIL-STD-901D Grade A, Class I, Type A	Shock
MIL-STD-461E	EMI/EMC

ENVIRONMENTAL SPECIFICATIONS


IP Rating	IP65 Drip Proof
Operating Temperature	0°C to 50°C
Storage Temperature	-20°C to +60°C
Humidity	10 to 90% @ RH Non-condensing



FRONT



SIDE



BOTTOM

DIMENSIONS INCHES MILLIMETERS

	INCHES	MILLIMETERS
Height	13.80"	351 mm
Width	23.00"	584 mm
Depth	2.90"	74 mm
Weight	20 lbs	9 kg